

Notice

1. This is a "Universal" child restraint. It is approved to regulation No. 44.03 series of amendments, for general use in vehicles and it will fit most, but not all car seats.
2. A correct fit is likely if the vehicle manufacturer has declared that the vehicle is capable of accepting a "Universal" child restraint for this age group.
3. This child restraint has been classified "Universal" under more stringent conditions than those which applied to earlier designs which do not carry this notice.
4. If in doubt, consult either the child restraint manufacturer or the retailer.
5. Only suitable if the approved vehicles are fitted with 3 point static or retractor safety belts, approved to UN/ECE Regulation No. 16 or other equivalent standards.


If you have a problem with this product or require any replacement parts, please contact your nearest Mothercare store or telephone the Mothercare Customer Care Line on 08453 30 40 30 alternatively write to:

Mothercare
Cherry Tree Road
Watford
Herts.
WD24 6SH
England

www.mothercare.com
Made in China



Flyte infant carrier user guide



دليل الاستخدام

Gebruikersgids

Guide de l'utilisateur

Οδηγός χρήσης

用户指南

Instrukcja użytkowania

Руководство пользователя

Folleto de instrucciones

Kullanım Kılavuzu

IMPORTANT! KEEP FOR FUTURE REFERENCE

Safety Warning


- Please read thoroughly before commencing installation as an incorrect installation could be dangerous.
- Do not use this child seat in passenger seats equipped with front airbags.
- Save this instruction manual in the storage compartment behind the seat cover for future reference.
- Make yourself familiar with these instructions and look carefully at the illustrations in the manual.
- The car safety seat offers maximum protection and is only safe when used in accordance with the instructions.
- For the safety of your child it is of crucial importance that the car seatbelt is threaded correctly. Follow the bright blue routing labels on the front belt hooks and ensure that the shoulder belt is also secured behind the bright blue belt hook at the rear of the seat.
- The car safety seat is approved in accordance with European safety standard (ECE R44/03) and is suitable for children from birth - 13kg (from birth to approximately 12-15 months old).
- The car safety seat may be used on the front or rear passenger seat, but always in a rearward facing position. DO NOT use a child safety seat where the vehicle is equipped with a front airbag. This can be dangerous. This does not apply to so-called side airbags. When using the car safety seat on a collapsible rear seat, always check to make sure the rear seat is locked securely before installing the car seat.
- The car safety seat must only be used on a forward facing seat fitted with an automatic 3-point seat belt, which is approved according to ECE R16 or an equivalent standard.
- Before purchasing the seat we recommend you to check if the car safety seat is compatible for use in your car.
- A baby can be very active. Do not be caught unawares by unexpected movements, and ALWAYS secure your baby with the harness belt, also when using the car safety seat out of the car. Do not allow yourself to be distracted by your child while driving.

Safety Warning

- We strongly advise you not to use a second-hand product, as you are never sure if the seat has been involved in an accident or whether it has been otherwise damaged.
- After an accident your car safety seat should be replaced. Although it may appear undamaged, if you were to have another accident it would not protect your child as well as it should.
- It is advisable not to use car safety seats longer than 5 years after the date of purchase. Due to the ageing process of the plastic for instance, the quality of the product may be unnoticeably deteriorated.
- Do not place the car safety seat on high surfaces, such as tables, worktops, beds, etc., due to the risk of falling.
- Under no circumstances may the moving parts of the car safety seat be oiled or greased.
- Ensure that all luggage/objects, on the parcel shelf for instance, likely to cause injury in the event of an accident are properly secured.
- Never leave your child unattended in the seat, either in or out of the car.
- When using the car safety seat on the front passenger seat, the car passenger seat must always be placed in the rearmost position. the backrest of the car seat must be placed in an upright position.
- The seat must always be secured with a seat belt, even when not in use.
- Ensure that the seat is not damaged by wedging it between or underneath heavy luggage, adjustable seats or slamming the car door, etc.
- No alterations may be made to the car safety seat, as this could effect part of the overall safety of the seat.
- The car safety seat must not be used without the cover. Always use an ORIGINAL car safety seat cover, as the cover contributes to the safety of the seat. the energy absorbing foam in the shell is essential for the safety and must not be removed.
- Do not remove the logo and the airbag warning label.

getting to know your child seat


fig 1



preparation for use

the type of approved seat belt you must have

fig 2



Your Mothercare child seat can only be installed rearward facing using a lap and diagonal seat belt in the front or rear passenger seat of the car.
DO NOT USE THIS CHILD SEAT IN PASSENGER SEAT EQUIPPED WITH FRONT AIRBAGS.

legal requirements

This child seat is approved to ECE R44.03 and is only suitable for use with 3 point lap and diagonal seat belts approved to UN/ECE Regulation No.16 or other equivalent safety standards

Front Seat: Anyone, especially children, travelling in the front seat of a car must be properly restrained. Children under three years must use a suitable approved restraint designed for their weight.


Rear Seat: All adults and children must use seat belts or child restraints where they are fitted in the rear of a car and are available for use. If the appropriate restraint is not available, children from 3 years must wear an adult seat belt if available.

important notes

- Keep this user guide in a safe place where it can easily be found.
- When the child seat is not in use, it is recommended that it is fastened into the car with a seat belt to avoid being thrown about in the event of an accident.
- In an emergency your child can be released quickly by pressing the red button on the harness buckle.
- If you travel with passengers using both the front and rear seats, the lighter occupants should be in the rear seats and the heavier occupants in the front of the vehicle. When a child is in the front seat, the lighter passenger should be behind the child.
- Do not allow the child seat to come into contact with corrosive substance e.g. battery acid

preparation for use


fig 3



The carrying handle has 3 positions. Press the two buttons on either side of the carrying handle simultaneously and move the carrying handle forwards or backwards as required. The buttons will pop out automatically and the indicators on the handle will be green when the carrying handle is in the correct position.

- 1 Carrying position/car position
- 2 Sleeping position/rocking position
- 3 Sitting position


fig 4



Open the harness buckle by pressing the red button. To close the harness place the left hand harness connector behind the right hand one **1** - they should slot together neatly. Push the harness ends in to the hole in the buckle at the top of the crotch strap **2**. you will hear and feel a "Click" when it is secure.

If you do not hear the "Click", press the red button to unlock and start again. If you are unable to fasten the harness system properly and tight enough, contact the supplier immediately and do not use the seat. Ensure the belts are not twisted or damaged. Periodically check that your child has not released the buckle. Ensure baby is seated correctly, it's back firmly against the back of the seat.

fig 5




Pull the harness adjuster belt at the front of the shell tight so that the child is firmly secured with the harness. It is recommended that there is just enough room to insert 1-2 fingers between the straps and your child's chest.

in use


adjusting the height of the shoulder straps

fig 6




The harness has 2 height positions. The straps should go in the slots closest above your child's shoulders. Make sure the harness fits tightly around the child's shoulders.

fig 7



To loosen the harness, press the quick adjuster button **1** at the front of the shell. Pull both harness shoulder belts simultaneously towards you **2**.

fig 8




To adjust the shoulder strap height, unlock the buckle and pull the shoulder belts through the slots in the cover and the shell. Thread the shoulder belts through the correct slots in the shell and cover. Ensure the harness is not twisted.

In use


Installation

fig 9




Note the difference between the lap belt and the diagonal belt when installing the seat in the car. Always place the seat in rearward facing position on a front or rear passenger seat, and adjust the carrying handle to the upright position. If the passenger seat belt is adjustable in height, place it in the lowest position. Ensure that the front seat is in the rearmost position. This does not apply if you are placing the child seat in the rear of the car

fig 10



Guide the lap belt of the 3-point seat belt through the blue marked lap belt guides on the front of the seat. Fasten the seat belt into the buckle.

fig 11




Place the cars diagonal belt around the back of the seat and hook it into the bright blue belt guide at the rear.

In use


Installation

fig 12



Ensure that the cars diagonal belt is behind the blue belt guide marked by the blue arrow and blocked by the retaining hook. Pull the belt tight. Ensure the belt is not twisted.

fig 13



Double check that the seat is threaded correctly through and underneath the three points marked by the blue arrows. The car safety seat is now correctly installed.

important

final checklist

However safe a child seat is, however well built it is, your child's safety depends on you. Read this final checklist once you have fitted your child seat in your car.

1. Check that you have adjusted the harness to suit your child. A fitting for winter clothes will be too loose for a child wearing summer clothes.
2. Check you have installed your child seat properly using a 3 point lap - see fig 7 - fig 11, Installation.
3. Check that your child seat is secure before each journey.
4. Make sure that there are no twists in the car seat belt.

REMEMBER: Misusing your child seat will reduce the protection and safety you offer your child.

Your child seat and its cover have been carefully designed, manufactured and tested to the highest safety standards.

Do not put your child's safety at risk by using without a seat cover. The seat cover should not be replaced with any other than the one recommended by Mothercare, because the cover constitutes an integral part of the restraint performance.

accessories

The safety of this seat may be compromised by the use of accessories not approved by Mothercare.